


▶ Product Appearance



▶ Product Size



Net Weight: 93.1±1kg

▶ Packaging Size



Gross Weight: 118±1kg


▶ Features

- A grade brand new Solid-State LiFePO₄ cells
- >5000 cycles @80% DOD(25°C, 0.5C)
- Over charge, over discharge, over temperature, low temperature, over current and short circuit protection
- Compatible with most inverters
- Stackable
- Cell balance function
- Max.8 battery packs can be connected in parallel
- Certificate: UN38.3 MSDS IEC62619 ROHS


▶ Technical Specifications

Model	LFP10.85KWH51.2V-P65F1QT50
Battery Type	LiFePO ₄
Nominal Voltage (V)	51.2
Nominal Capacity (AH)	212
Energy (WH)	10854
Pack Mode	16S4P
Continuous Discharge Current (A)	100
Charge Cut-off Voltage (V)	57.6
Discharge Cut-off Voltage (V)	41.6
Max.Charge Current (A)	100
Max.Discharge Current (A)	200
Peak Discharge Current (A)	240@2S
Recommend Discharge Current (A)	100
Recommend Discharge Depth (%)	80
Cycle Life	>5000 cycles (25°C, 0.5C) 80% DOD
Communication	CAN RS485 RS232
Display	LED
Charge&Discharge Temperature (°C)	Charge: 0°C~+55°C / Discharge: -20°C~+60°C
Optimal Storage Temperature (°C)	5°C ~ +35°C
Recommend Storage Humidity	60%±20% RH
Terminal	Quick-connector
Dimensions (L*W*H) (mm)	601*160*885
Weight (Kg)	93.1±0.5
Certificate	UN38.3、MSDS、IEC62619、ROHS
IP Class	IP65


Different Rate Discharge Curve@25°C




Different Temperature Discharge Curve@0.5C




State of Charge Curve@0.5C 25°C



Charging Characteristics @0.5C 25°C



Different DOD Discharge Cycle Life Curve@0.5C 25°C



Different Temperature Self Discharge Curve

